

RV WindSkirt Installation Instructions

(Installation of the Velcro onto your vehicle is a one-time application)

1. Identify the area that you will be attaching the Skirt Panel to. Make sure that the attachment points are not above the fully extended height of the Skirt Panel the Skirt should easily touch the ground and still have some give. This will allow for the best wind blocking seal on even or uneven ground surface.
2. Identify and mark the points on the vehicle at least every 6 inches on center, for the fifth wheel skirts, place every 3 inches, this will allow for a secure attachment. Best to use masking tape to get a straight line. **Do Not Place Velcro On Any Decal Or Vinyl.** (You can mark a round line around the Velcro patch on the decal or vinyl, cut out the area before applying patch if you want to. Entirely up to you)
3. Once all attachment points have been identified and marked, Clean very well with isopropyl Alcohol 90% or a safe solvent (Acetone) using a cotton ball or clean wipe towel. Wipe dry after cleaning to remove any leftover residue using a dry paper towel or cleaning towel. Ideal install temp 70°F. Remove the protective cover off the Velcro patch and place firmly onto the unit. Must adhere for 48-72 hours for full strength of adhesive. Repeat until you have all the Velcro patched on the unit.
4. If outside temperature of 70°F isn't possible, you may use a hairdryer to warm the spot of placement, then adhere the Velcro patch over the warm area.
5. Remove Skirt from package and unfold, place skirts along unit and attach.
6. If you will be using multiple Skirt Panels, you will attach the Velcro portion of the next skirt over the Velcro part of the previous skirt and just repeat the process.
7. Once all the Skirt Panel are firmly attached to the unit, you can place the weighted material, i.e. sand, rounded rocks or our water weight bags into the patent Skirt pouches.
8. Never Place Sharp Objects into Pouches or Place Skirt onto rough/sharp ground

“The Velcro Patches that stick onto the unit are guaranteed for 5 years”

If you require assistance, call our customer service help line 800-591-4737

**Caution – Do not install Skirt over any heat source or hot gases that exit any part of the vehicle; exhaust pipes, hot water heaters & heaters
Due to a possible fire hazard**